

MSP 226

H.264 to HDMI Mini Converter



Key Features

- 1U Frame
- H.264 Input
- HDMI 1.3 Output
- Controlled by USB

Specification

| | | |
|--------------------|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connectors | Inputs | 2× H.264 (RJ45) |
| | Outputs | 2× HDMI (HDMI-A) |
| | Remote Control | USB |
| | Power | 5.4mm DC Socket |
| Performance | Input Resolution | 176x144 240x180 320x180 320x240 320x256 352x228 352x480 400x224 400x320 480x270 480x272 480x320 480x360 480x384 480x480 544x480 608x448 640x360 640x480 704x576 720x404 720x480 720x540 720x576 850x480 1024x576 1280x720 1680x1056 1920x1080 Refresh Rates 10~60FPS |
| | Output Resolution | VESA: 800x600x60 1024x768x60 1280x800x60 1280x1024x60 1366x768x60 1440x900x60 1600x1200x60 1680x1050x60 1920x1080x60 SMPTE: 480i60 576i50 720P50/59.94/60 1080i50/59.94/60 1080P25/29.97/30/50/59.94/60 |
| | Supported Standards | HDMI 1.3 H.264 H.264/MPEG-4 AVC |
| | Encoding Protocols | H.264 baseline/main/high profile L4.2 MJPEG/JPEG baseline |
| Power | Input Voltage | 12V DC (via universal Plug Pack) |
| | Max Power | 1A |
| Environment | Temperature | 0°C~45°C |
| | Humidity | 10%~85% |
| Physical | Weight | 0.27kg (Net Weight) |
| | Dimensions | 98mm x 92.9mm x 44mm (Device Dimension) |

Order Codes

| Product Code | Item |
|---------------|-------------------------|
| 600-0226-01-1 | H.264 to HDMI Converter |

Dimensions

