



# mini-mx-2s-subito

## All-In-One Portable Case for mini-mx

This Dedicated Portable Case made of high-strength PP material is equipped with a 13.3-inch IPS display and a switcher. Integrated audio and video switching, PTZ camera control, multi-view monitoring, and recording in one case, this portable and shock-resistant carry case is perfect for all sites, from music festival to lawn wedding, sports competition and other outdoor activities.












### **Key Features**

- Professional aviation connector to ensure high-quality performance
- · Flexible standard connectors to meet personalized application
- Built-in 13.3" HD IPS monitor
- High strength PP flightcase features long-lasting durability
- hydraulic rod support to enhance the stability
- Powerful air-cooling system designed for outdoor use
- 4K multi-channel streaming video mixer
- Built-in 5.5 inch touch screen for menu operation
- Quad HDMI 2.0 inputs, resolutions up to 4K@60
- Dual HDMI 1.3 outputs for monitoring of multi-window PVW and PGM
- . Dual MIC in, one Line-in, one Bluetooth in, dual audio out
- Mix for HDMI embedded and external audio
- One-key recording. Recording capacity of hard drive is up to 2T
   Support simultaneous streaming to 2 live streaming platforms via RTMP(S)
- Support multi-layer overlay, layer scaling and cropping
- 15 switching effect modes
- 5-direction joystick for controlling up to 4 PTZ cameras
- Save and store up to 16 scene presets. One-click for preset recall
- Support web control, compatible with mobile devices and computers, compatible with multiple operating systems
- Support Chroma Key
- One-key quick switch between portrait and landscape screen
- XPOSE control

### Application



#### Specification

Connectors Input HDMI 4K SDI UVC (webs) Output HDMI 2K SDI UVC UVC UVC (webs) UVC UVC (webs) LAN (strean LAN (stre	2×HDMI-A 2×BNC :am) 1v.SB-C
Output HDMI 2K SDI UVC USB (recor LAN (strea	
Output HDMI 2K SDI UVC USB (recor LAN (strea	am) 1×USB-C
SDI UVC USB (recor LAN (strea	
UVC USB (recor LAN (strea	1×HDMI-A
USB (recor LAN (strea	1×BNC
LAN (strea	1×USB-C
	d) 1×USB-C
	m) 1×RJ45
LAN (subit	o) 4×RJ45
Audio In MIC 1	1×CANNON Jack (XLR)
MIC 2	1×CANNON Jack (XLR)
LINE	1×6.35mm TRS Jack
Bluetooth	1×Bluetooth Module
HDMI	2×HDMI-A
SDI	2×BNC
Audio Out AUDIO	1×6.35mm TRS Jack
	1×3.5mm mini-Jack
HDMI	1×HDMI-A
SDI	1×BNC
UVC	1×USB-C
LAN	1×RJ45
USB (recor	d) 1×USB-C
Control USB (subit	o) 1×USB-B
Performance Input Resolution HDMI	1280×720@50/59.94/60   1024×768@60   1280×768@60   1280×800@60   1280×1024@60   1360×768@60
	1366×768@60   1440×900@60   1600×1200@60   1680×1050@60   1920×1200@60   1920×1080i@50/59.94/60
	1920×1080p@23.98/24/25/29.97/30/50/59.94/60   3840×2160p@30/50/60   4096x2160@30/50/60
SDI	1080P@23.98/24/25/29.97/30/50/59.94/60
Output Resolution HDMI	1280×720@50/60   1024×768@60   1280×768@60   1280×1024@60   1360×768@60
	1920×1080@23.98/24/25/29.97/30/50/59.94/60
SDI	1080P@23.98/24/25/29.97/30/50/59.94/60
USB (Web	cam) 1920×1080@24/25/30/50/60
Video Video Forn	nats HDMI 2.0   HDCP 2.2
Grayscale	Processing 10bit
Video Sam	pling 4:4:4 YUV
Video Late	ncy <4 frames
Audio Line In Del	ay up to 8 frames
Audio Forn	nat HDMI Linear PCM, 24 bits/48 kHz, 2 ch
	USB Linear PCM, 16 bits/48 kHz, 2 ch
Record/Storage Record For	
Disk Forma	
Supported Standards HDMI	2.0
USB	3.0
H.265	ITU-T H.265/ ISO/IEC 23008-2
13.3" Display Screen Size 13.3"	
Panel Type IPS	
	%NTSC/:16.7M, 100%sRGB
Resolution 1920×1080	) pixels
Aspect Ratio 1000:1	
Gamut 72%	
Brightness 350 cd/m <sup>2</sup>	
Refresh Rate 60Hz	
	R) 85°/85°(U/D)
Subito RJ45(each port)	
Subito RJ45(each port) Capacity 655,360 pi	
Subito         RJ45(each port)           Capacity         655,360 pi           Horizontal Range         3840 pixel	
Subito   RJ45(each port)   Capacity   655,360 pi   Horizontal Range   3840 pixel   Vertical Range   2048 pixel	
RJ45(each port)   Capacity   655,360 pi   Horizontal Range   3840 pixel   Vertical Range   2048 pixel   Power   Input Voltage   PD 12V/5A	
RJ45(each port)   Capacity   655,360 pi	
RJ45(each port)   Capacity   655,360 pixel   Horizontal Range   3840 pixel   Vertical Range   2048 pixel   Power   Input Voltage   PD 12V/5#   Maximum Power   60W   Physical   Outer Size   460mm × 3   3   3   3   3   3   3   3   3   3	
RJ45(each port)   Capacity   655,360 pi   Horizontal Range   3840 pixel   Vertical Range   2048 pixel   Power   Input Voltage   PD 12V/5#   Maximum Power   60W   Physical   Outer Size   Material   PP   PP   Maximum Power   Material   PP   P   P   P   P   P   P   P   P	
Subito	
RJ45(each port)	

#### **Order Codes**

Order Codes	Item
230-0004-08-0	mini-mx-2s-subito
	(1 × mini-mx + 1 × Flightcase Suite
	+ 1 × 13.3" Display + 1×subito Sending Card)

#### Contact us

Tel: +86-592-5771197 Fax: +86-592-5788216 E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China



