

RGBlink vue PTZ camera

RGB20X-USB-TLY



Front View



Rear View

Key Features

- High speed optical zoom
- RTSP/RTMP/SRT encoding output
- High performance in low light scenarios with Wide Dynamic Range
- Full 1920x1080p HD Resolutions up to 60 frames per second
- H.265/H.264 Dual Stream Output Adapted to Different Network Environments
- Pan and Tilt Control
- Applicable to meeting, live streaming, church, classroom and more
- Low-power Sleep Function
- Support TALLY
- Support PoE

Specification

Interface	Output	HDMI	1xHDMI-A
		USB 2.0	1xUSB-A
		USB 3.0	1xUSB-A
		LAN	1xRJ45
	Audio	IN	1x3.5mm Stereo Jack
	Control	RS232	1xDIN8
	Power		1xDC 12V Jack
Performance	Camera		20X
		Optical Zoom	f= 4.8~96mm
		View Angle	3.45°~ 60.04°
		AV	F1.8 ~ F2.9
		Digital Zoom	10X
		Minimum Illumination	0.5Lux (F1.8, AGC ON)
		DNR	2D & 3D DNR
		White Balance	Auto/Manual/One Push/3000K to 7000K(selectable)
		Focus	Auto/Manual
		Aperture/Electronic Shutter	Auto/Manual
		BLC	ON/OFF
		WDR	OFF/Dynamic Level Adjustment
		Video Adjustment	Brightness/Color/Saturation/Contrast/Sharpness/B/W mode/Gamma curve
		SNR	>55dB
	Effective Pixels	2.07 megapixels	
Sensor	1/2.8 inch HD CMOS		
Pan-and-Tilt Parameter	Pan/Tilt Movement	-170°~+170°/-30°~+90°	
	Pan/Tilt Control Speed	0.1~60°/S; 0.1~30°/S	
	Preset Speed/Quantity	Pan:60°/S; Tilt:30°/S; Up to 255 preset positions (10 remote control)	
	360° TALLY	full 360° view of TALLY	
Audio Compression Format	AAC MP3 G.711A		
Video Compression Format	H.264 H.265 Dual Streaming Output		
Output Resolutions	1080p60/59.94/50/30/29.97/25 1080i60/59.94/50 720p60/59.94/50		
Control Protocol	VISCA Pelco-D Pelco-P ONVIF		
Baud Rate(bps)	115200 9600 4800 2400bps		
Network Protocol	RTSP RTMP ONVIF		
Power	Input Voltage	DC12V/1.5A	
	Max Power	12W	
Environment	Temperature	-10℃~50℃	
	Humidity	20%~80%	
Physical	Weight	Net	1.7kg
	Dimension	Net	180mm(front)×188mm(side)×198mm(height)

Order Codes

Product Code	Item
981-0011-29-0	RGB20X-USB-TLY, 20X USB PTZ Camera with TALLY

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

Specifications are correct at time of printing and subject to change or alteration without notice.



www.rgbink.com