



MSP 325N

UHD 4K HDMI Video Encoder

The MSP 325N is a high-performance, compact streaming processor that combines exceptional portability with powerful features.

Its sleek, small design makes it easy to carry and versatile enough for various scenarios. Supporting H.265/H.264 high-efficiency encoding to ensure excellent video quality while minimizing bandwidth usage.

The MSP 325N handles input resolutions up to 4K@60Hz, making it ideal for high-resolution video processing. It is compatible with a range of streaming protocols including HTTP, SRT, RTMP, RTSP, and NDI, catering to diverse streaming needs.

Additionally, the MSP 325N also features USB connectivity for video recording, allowing users to replay content anytime, offering enhanced flexibility. With PoE power support and TAO cloud integration control, installation and management are simplified. The low-latency transmission makes the MSP 325N an ideal choice for live streaming, conference, and other video IP transmission applications.



H.265/ H.264 Encoder



4K@60Hz Input



HTTP/ SRT/ RTMP/
RTSP/NDI



TAO Cloud



PoE




Portable

Key Features


- Small and compact, easy to carry
- H.265/H.264 high-performance encoding capability
- Input resolution up to 4K@60Hz
- HTTP/SRT/RTMP/RTSP/NDI protocols supported

- Feature with one USB interface for recording
- PoE & DC 12V power supply
- TAO Cloud integrated control
- Low latency transmission

Application



Dimensions



unit: mm

Specification

Interface	Input	HDMI 2.0	1×HDMI-A
	Output	HDMI 2.0	1×HDMI-A (LOOP)
	Audio	Line-in	1×3.5mm Audio Jack
	Ethernet/Upgrade/Stream	LAN	1×RJ45
	Storage	USB	1×USB-A
	Power	Power	1×DC Jack
	Performance	Input Resolution	HDMI 2.0
Format			RGB/YUV 4:4:4/YUV 4:2:2 8bits/10bits/12bits
Deinterlacing			YES
Embedded Audio			YES
HDCP			2.2/1.X
Output Resolution		HDMI 2.0	720p@50 1920×1080i@50/60 1920×1080p@24/30/50/60 3840×2160@30/50/60
Audio Input		Audio Mixing	YES
		Analog Audio Input	LINE IN
Record		Video	H.264, up to 32Mbps
		Audio	AAC, up to 48Kbps
Storage	Built-in Storage	128GB	
Encoding	Performance	H.264/H.265	
	Protocols	HTTP/SRT/RTMP/RTSP/NDI	
	Resolution	up to 3840×2160p@60	
Power	DC Input	12V/2A	
Working Environment	Temperature	0°C~55°C	
	Humidity	5%~85%	
Physical	Net Dimension	165mm × 106.4mm × 28mm	

Order Codes

Product Code	Item
410-5513-06-1	MSP 325N

Contact us

Tel: +86-592-5771197

Fax: +86-592-5788216

E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3,

Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

RGBlink
www.rgblink.com

