


2025 **MSP 325N**



UHD 4K HDMI Video Encoder/Decoder

H.265 | H.264 | HTTP | SRT | RTMP | RTSP | NDI | PoE



RGBlink




ONE DEVICE FOR THE WORLD

There's no streaming media processor more compact and portable than this

Encoding and Decoding


PlayStation 5/Pro, Xbox Series X, Switch, Steam Deck, ROG Ally, PC, Mac,
Works seamlessly with virtually any device, including industrial computers, players,
cameras, set-top boxes, and even iPhones.



Camera, monitors, workstations, laptops, desktops, TV boxes, PS5, XBOX, Switch

USB Camera

Active microphone



Live streaming platform



TikTok



Youtube



Twitch



Facebook

.....



Internet streaming

Switches/ Routers

True 4K60 codec

Multi-channel video synchronous decoding



Low Latency



Live Broadcast Agreement
HTTP/ SRT/ RTMP/RTSP/NDI



4K IN/OUT



H.265



Web Control



4K Codec


EASY INSTALLATION, STABLE AND DURABLE.

Customers can purchase a hanging accessory (compatible with the mounting holes on the back of the monitor). This accessory allows you to conveniently hang the device from the back of a monitor or directly attach it to a wall, cabinet, or other flat surface for even greater convenience.




EASY INSTALLATION

The product features a 1/4-inch universal screw hole and hot shoe mount, making it easy to attach to tripods, cameras, cages, and other equipment.



Local web management

Make operations more intuitive, management more efficient, and smarter!



ENCODING AND STREAMING

Compress the video signal from an HDMI device into a network signal, output it through the network port, and send it to other devices or live streaming platforms.

You can also record audio and video and save them to a USB drive or hard drive.



Camera, monitors, workstations, laptops, desktops, PS5



Live broadcast/streaming

HTTP、SRT、RTMP、RTSP、NDI



DECODING AND DISPLAY

Receives network audio and video streams through the Ethernet port, decodes them, and outputs them to a display device through the HDMI port.



Display device/
director console



Pull/Push Stream

HTTP、SRT、RTMP、RTSP、NDI

Video Stream Protocol Conversion

Supports multiple protocol conversions, including RTSP to RTMP. The product supports conversion between any supported protocols.

RTSP



RTMP/SRT/NDI

Transcoding

Easily convert between H.264 and H.265. Easily handle audio encoding as well.


H.264+PCM



H.265+AAC

Matching ASK nano

Realize wireless image transmission




MULTI-PLATFORM LIVE STREAMING ENCODING MULTI-PARTY PUSH

Simultaneous audio and video streaming, unlimited connections across multiple platforms, and smooth live streaming!



Multi-platform live streaming



Game live streaming/recording

Supports multiple input interfaces and mixed audio and video encoding, Picture-in-picture, and multi-screen splicing.




Live/recorded online classes

Supports multiple input interfaces and mixed audio and video encoding, Picture-in-picture, and multi-screen splicing.



Smooth every frame

Common encoders only retain half the frame rate during deinterlacing, causing stuttering. RGBlink proprietary full-frame-rate deinterlacing algorithm perfectly restores every frame, ensuring smoother, full-frame data. Say goodbye to blur and embrace HD, ensuring every detail is as clear as ever.



Comprehensive protocols

Supports multiple input interfaces and mixed audio and video encoding, Picture-in-picture, and multi-screen splicing.

NDI[®] | HX

No additional charge

SRT

Low latency, high efficiency,
strong software compatibility

RTMP/ RTSP

Enhanced security
Widely used

Product Specifications

 Net Weight: 330g



139mm



99.5mm

27.6mm

*no mounting ear

Specification

Interface	Input	HDMI 2.0	1 × HDMI-A
	Output	HDMI 2.0	1 × HDMI-A (Loop)
		HDMI 2.0	1 × HDMI-A
	Audio	Line-in	1 × 3.5mm Audio Jack
	Capture	USB	1 × USB-A
	Storage	USB	1 × USB-C
	Ethernet/Upgrade/Stream	LAN	1 × RJ45
	Power	Power	1 × DC socket
Performance	Input Resolution	HDMI 2.0	720p@50 1920 × 1080i@50/60 1920 × 1080p@24/30/50/60 3840 × 2160@30/50/60
		Format	RGB/YYUV 4:2:2 8bits
		Deinterlacing	YES
		Embedded Audio	YES
		HDCP	2.2/1.X
	Output Resolution	HDMI 2.0	720p@50 1920 × 1080i@50/60 1920 × 1080p@24/30/50/60 3840 × 2160@30/50/60
	Audio Input	Analog Audio Input	LINE IN
	Record	Video	H.264, up to 32Mbps
		Audio	AAC, up to 48Kbps
	Storage	Built-in Storage	128GB
	Encoding	Performance	H.264/H.265
		Protocols	HTTP/SRT/RTMP/RTSP/NDI
		Resolution	up to 3840 × 2160p@60
	Decoding	1 × 4K@60Hz, 2 × 4K@30Hz, 4 × 2K@60Hz	
Power	DC Input	12V/2A	
Working Environment	Temperature	0°C~55°C	
	Humidity	5%~85%	
Physical	Net Weight	0.33kg	
	Package Weight	0.96kg	
	Net Dimension	139mm × 99.5mm × 27.6mm	
	Package Dimension	255mm × 147mm × 88mm	

*no mounting ear

Order code

Product code	Name
601-0325-05-1	MSP 325N

