



## Specification

<b>Interface</b>	USB 2.0	1 × Type-C		
	Tripod Screw Hole	ISO 1222 1/4 inch screw		
<b>Performance</b>	Sensor Type	1/2.55" SONY Sensor		
	Diagonal Field of View	FoV(H): 73° (EFL:25mm) FoV(D): 78°		
	Digital Zoom	1.5X (Disabled at 4K/1080P@60fps)		
	Lens	Imaging lens: 5PAI lens: 6P		
	Aperture	F1.8 (imaging)		
	Focus Mode	Auto Focus + AI Tracking		
	Focus Distance	10-300cm		
	Resolution	USB2.0		
		MJPEG (Default first)	3840×2160@30fps (4K, default, no zoom)   2560×1440@30fps   1920×1080@30/60fps (no zoom @60fps)	
			1280×960@30fps   1280×720@30/60fps   1024×576@30/60fps   960×720@30fps   800×600@30fps	
	YUV	640×480@30fps   640×360@30/60fps		
	Gimbal - Horizontal	Manual:	310°	
		Motorized:	300° (Non-detachable)	
	Gimbal - Vertical	Manual:	180°	
		Motorized:	180° (Non-detachable)	
Gimbal Rotation Speed	Tracking (max):	100°/s		
	Fine-tuning (min):	60°/s"		
Audio	Microphones	3-mic array		
	Frequency Response	100-10KHz		
	Noise Reduction Algorithm	√ ( Live Streaming/Original/Noise Cancellation Mode)		
	Call Distance	8ft (recommended)		
Video Format	YUY2 / MJPEG			
<b>Compatibility</b>	Hardware	2.4 GHz Intel® Core 2 Duo processor or higher 2 GB RAM or higher USB 2.0 port		
	System	Windows (Win10 and above; 64-bit only), macOS (10.14 and above). With USB port, works in USB video device class (UVC) mode, Linux		
	Software	Domestic: DouYu, HuYa, YY Live, Kuaishou, Douyin, OBS; Overseas: OBS, Twitch, YouTube, Facebook, XSplit, ManyCam		
<b>Power</b>	Input Voltage	5V		
	Input Current	500mA (max)		
	Power Consumption	2W (max)		
<b>Cable</b>	USB 2.0 C to C	1 × 1.5m		
<b>Working Environment</b>	Operating Temperature	0°C ~ 40°C		
	Storage Temperature	-10°C ~ 65°C		
<b>Physical Parameters</b>	Privacy Cover	N/A (Privacy Mode)		
	Net Dimension	53 × 53 × 73mm ±1mm		
	Package Dimension	144 × 72 × 93mm		
	Net Weight	120±5g		
	Package Weight	325.5±5g		
	Packing Quantity	40pcs / CAR		
	Outer Box Dimensions	395 × 390 × 310mm ±5mm		
	Outer Box Gross Weight	14.13 kg±0.5kg		

## Order Codes

Product Code	Item
981-0011-81-1	tinyZ

## Contact us

Tel: +86-592-5771197

Fax: +86-592-5788216

E-mail: sales@rgblink.com

Headquarter: Room 601A, No. 37-3 Banshang community, Building 3, Xinke Plaza, Torch Hi-Tech Industrial Development Zone, Xiamen, China

**RGBlink**  
www.rgblink.com

